

TX-PNSY/WPCA-BS5534-25x50-TFT



SR TIMBER
BS 5534 : 2014

PREMIUM GOLD

QUALITY ROOFING BATTENS

PRODUCT DATA SHEET

FULLY GRADED ROOFING BATTEN TO BS 5534:2014

- SR Timber Vacsol PREMIUM GOLD® is our highest grade of roofing batten, incorporating a unique and distinctive gold colouration that does not hide any potential defects that can be found within traditional battens.
- SR Timber Vacsol PREMIUM GOLD® roof battens are produced to the highest standards in Latvia, then imported as a finished product to our timber terminal on the Humber.
- Fully compliant to all relevant standards – BS 8417:2003 (Preservation of Timber) and BS 5534:2014.
- Manufactured full to size in both **thickness** and **depth**.
- Available in both 25mm x 38mm and 25mm x 50mm profiles and lengths from 3.0m up to 5.4m.
- Produced from the highest grade, slow grown spruce (Whitewood) Picea abies – WPCA or pine (Redwood) Pinus sylvestris – PNSY, all supplied from either FSC® or PEFC fully certified or controlled resources.
- Raw material is pre-graded prior to processing to enable an even higher finished grade of roofing batten.
- Visually piece graded by our own qualified staff to fully comply to BS 5534:2014. This grading process is third party assessed and audited twice a year by Technology For Timber Ltd to ensure continued compliance to BS 5534:2014 and random quality checks by BM TRADA.
- By visual grading we are controlling the following defects:
 - Dimension
 - Size and Quantity of Knots
 - Wane
 - Fissures and Splits (check for end splits on site)
 - Slope of Grain
 - Rate of Growth
 - Decay and Insect Attack
 - Size of Resin Pockets
- Battens are dried in order to comply with the correct moisture content as recommended by British Standards and should not exceed 22% moisture content at time of fixing.
- Individually piece marked and full colour identity, as required by BS 5534:2014.
- Vacsol Aqua preservative treated to BS:8417:2003 with our standard 60 year lifetime warranty against insect attack and wood rotting fungi (when used correctly and installed above dpc level in buildings).
- This latest generation preservative treatment process ensures the battens are lighter in weight than standard treated battens.



SR TIMBER
TIMBER SPECIALISTS

SR Timber, Nunn Brook Road
Huthwaite, Sutton-in-Ashfield
Nottinghamshire NG17 2HU

Tel: **01623 446800**

Fax: **01623 440347**

E: **sales@sr-timber.com**

www.sr-timber.com



Promoting Sustainable
Forest Management
www.pefc.co.uk



The mark of
responsible forestry