

IMPORTED

QUALITY SOFTWOOD TIMBER

SPRUCE & PINE PRODUCTS

PRESSURE TREATED

Traditional Timber Dimensions

19x38mm (¾" x 1½")	47x125mm (2" x 5")	75x75mm (3" x 3")
19x50mm (¾" x 2")	47x150mm (2" x 6")	75x100mm (3" x 4")
25x38mm (1" x 1½")	47x175mm (2" x 7")	75x125mm (3" x 5")
25x50mm (1" x 2")	47x200mm (2" x 8")	75x150mm (3" x 6")
38x38mm (1½" x 1½")	47x225mm (2" x 9")	75x175mm (3" x 7")
38x50mm (1½" x 2")	50x50mm (2" x 2")	75x200mm (3" x 8")
47x100mm (2" x 4")	50x75mm (2" x 3")	75x225mm (3" x 9")

Speciality Timber Dimensions

6x25mm Counterbatten / Plasterboard Lath

11x38mm Counterbatten

12x38mm Drip Batten

50x50mm Corner to Corner (Arris Rail)

50x75mm Corner to Corner (Arris Rail)

50x50mm Mopstick (Lead Roll)

- SR Timber "IMPORTED" products are manufactured at our own sawmill as well as carefully selected 3rd party production plants. Timber products should be protected whilst in store to prevent water saturation, this will prevent sagging or twisting of the material.
- SR Timber "IMPORTED" products are available in various lengths ranging from 2.4m up to 5.4m, in 300mm increments.
- Produced from imported spruce (Whitewood) Abies Alba/Picea abies – WPCA or pine and (Redwood) Pinus sylvestris – PNSY or combined/ mixed species – WPPA, all supplied from either FSC® or PEFC™ fully certified or controlled wood resources. All "IMPORTED" products also meet all requirements within EUTR regulations.
- High pressure Tanalith E preservative treated to class 2, as in accordance with recommendations given in BS 8417. All SR Timber "Imported" products carry our standard 60 year service life certification, against insect attack and wood rotting fungi (when used correctly and installed above dpc level in buildings).



SR Timber, Nunn Brook Road
 Huthwaite, Sutton-in-Ashfield
 Nottinghamshire NG17 2HU

Tel: **01623 446800**

Fax: **01623 440347**

E: **sales@sr-timber.com**

www.sr-timber.com