

TX-PNSY/WPCA-BS5534-25x50-TFT



SR TIMBER
BS 5534 : 2014

PREMIUM GOLD

QUALITY ROOFING BATTENS

FULLY GRADED ROOFING BATTEN TO BS 5534:2014

- SR Timber Vacsol PREMIUM GOLD® is our highest grade of roofing batten, incorporating a unique and distinctive gold colouration that does not hide any potential defects that can be found within traditional battens.
- SR Timber Vacsol PREMIUM GOLD® roof battens are produced to the highest standards in Latvia, then imported as a finished product to our timber terminal on the Humber.
- Fully compliant to all relevant standards – BS 8417:2003 (Preservation of Timber) and BS 5534:2014.
- Manufactured full to size in both **thickness** and **depth**.
- Available in both 25mm x 38mm and 25mm x 50mm profiles and lengths from 3.0m up to 5.4m.
- Produced from the highest grade, slow grown spruce (Whitewood) Picea abies – WPCA or pine (Redwood) Pinus sylvestris – PNSY, all supplied from either FSC® or PEFC fully certified or controlled resources.
- Raw material is pre-graded prior to processing to enable an even higher finished grade of roofing batten.
- Visually piece graded by our own qualified staff to fully comply to BS 5534:2014. This grading process is third party assessed and audited twice a year to ensure continued compliance to BS 5534:2014 and random quality checks by BM TRADA.
- By visual grading we are controlling the following defects:
 - Dimension
 - Size and Quantity of Knots
 - Wane
 - Fissures and Splits (check for end splits on site)
 - Slope of Grain
 - Rate of Growth
 - Decay and Insect Attack
 - Size of Resin Pockets
- Battens are dried in order to comply with the correct moisture content as recommended by British Standards and should not exceed 22% moisture content at time of fixing.
- Individually piece marked and full colour identity, as required by BS 5534:2014.
- Vacsol Aqua preservative treated to BS:8417:2003 with our standard 60 year lifetime warranty against insect attack and wood rotting fungi (when used correctly and installed above dpc level in buildings).
- This latest generation preservative treatment process ensures the battens are lighter in weight than standard treated battens.



PRODUCT DATA SHEET



SR TIMBER
TIMBER SPECIALISTS

SR Timber, Nunn Brook Road
Huthwaite, Sutton-in-Ashfield
Nottinghamshire NG17 2HU

Tel: **01623 446800**

Fax: **01623 440347**

E: **sales@sr-timber.com**

www.sr-timber.com



Promoting Sustainable
Forest Management
www.pefc.co.uk



The mark of
responsible forestry