

# IMPORTED

## QUALITY SOFTWOOD TIMBER

# SR TIMBER

## IMPORTED

### QUALITY SOFTWOOD TIMBER

## SPRUCE & PINE PRODUCTS

### PRESSURE TREATED

#### Traditional Timber Dimensions

##### UG Sawn

19x38mm      19x50mm      25x38mm      25x50mm

##### Carcassing UG, C16/24

47x50mm      UG      47x75mm      C16/24

##### Carcassing C24

47x100mm      47x125mm      47x150mm      47x175mm

47x200mm      47x225mm      47x250mm

75x100mm      75x150mm      75x200mm      75x225mm

#### Speciality Timber Dimensions

6x25mm Counterbatten / Plasterboard Lath

11x50mm Counterbatten

12x38mm Drip Batten

50x50mm Corner to Corner (Arris Rail)

50x100mm Corner to Corner (Arris Rail)

50x50mm Mopstick (Lead Roll)

- SR Timber "IMPORTED" products are manufactured at our own sawmill as well as carefully selected 3rd party production plants. Timber products should be protected whilst in store to prevent water saturation, this will assist in preventing sagging or twisting of the material.
- SR Timber "IMPORTED" products are available in various lengths ranging from 2.4m up to 5.4m, in 300mm increments. Carcassing is available from 2.4m up to 6.0m in 600mm increments.
- Produced from imported spruce (Whitewood) Abies Alba/Picea abies – WPCA or pine and (Redwood) Pinus sylvestris – PNSY or combined, all supplied from either FSC® or PEFC™ fully certified or controlled wood resources.
- High pressure Tanalith E preservative treated to use class relevant to the product type, as in accordance with recommendations given in BS 8417:2011+A1:2014. All SR Timber "Imported" products carry our standard 60 year service life certification, against insect attack and wood rotting fungi (when used correctly and installed above dpc level in buildings).



# PRODUCT DATA SHEET



SR Timber, Nunn Brook Road  
Huthwaite, Sutton-in-Ashfield  
Nottinghamshire NG17 2HU

Tel: **01623 446800**  
Fax: **01623 440347**  
E: [sales@sr-timber.com](mailto:sales@sr-timber.com)

[www.sr-timber.com](http://www.sr-timber.com)

