

BLUE LABEL 5X CERTIGRADE WESTERN RED CEDAR SHINGLES

- These shingles are lightweight and practical. It advised to check NFRC technical guidance notes on fixing cedar shingles and if treatment advised, this tends to be calculated on geographical location of which the product is to be fixed. Good practice is to also follow specification and fixers advice.
- After weathering they will adopt a silvery grey shade.
- Cedar is naturally insect & rot resistant requiring no further treatment and sourced from sustainable forests in Western Canada.
- Western Red Cedar.
- Backed by The Cedar Shake and Shingle Bureau.

Colour	<i>Natural, varying reddish brown to pale yellow</i>
Grade	<i>Blue Label, 100% Heartwood, 100% Edge Grain and 100% Clear</i>
Size	<i>400mm long, random widths 75mm - 350mm</i>
Thickness	<i>10mm at the butt, tapering</i>
Profile	<i>Sawn both sides, rectangular</i>
Max. Pitch	<i>90°</i>
Min. Pitch	<i>14°</i>
Min. Side Lap	<i>38mm</i>


Pitch	Max Gauge	Coverage m² per bundle
<i>90°</i>	<i>190mm</i>	<i>3.47</i>
<i>22 - 90°</i>	<i>125mm</i>	<i>2.28</i>
<i>14 - 22°</i>	<i>95mm</i>	<i>1.73</i>

- Recommended fixings are 31mm x 1.8mm annular ring nails in stainless steel.
- Each shingle should be fixed with two nails.
- As a rule of thumb 1kg of nails will be required for every 4 bundles of shingles.

Recommended Roofing battens SR Gold BS 5534:2014 + A2:2018

<i>90°</i>	<i>25 x 50</i>	<i>5.3m - Battens per m2</i>
<i>450mm centres</i>	<i>25 x 38</i>	<i>8.0m - Battens per m2</i>
<i>600mm centres</i>	<i>25 x 38</i>	<i>10.5m - Battens per m2</i>

- We recommend that gloves are worn at all times when handling timber products.



PRODUCT DATA SHEET



SR Timber, Nunn Brook Road
Huthwaite, Sutton-in-Ashfield
Nottinghamshire, NG17 2HU

T: 01623 446800

E: sales@sr-timber.com

sr-timber.com