

IMPORTED

QUALITY SOFTWOOD

TIMBER

SR TIMBER

IMPORTED

QUALITY SOFTWOOD TIMBER

SPRUCE & PINE PRODUCTS

PRESSURE TREATED

Traditional Timber Dimensions

UG Sawn

19x38mm 19x50mm 25x38mm 25x50mm

Carcassing UG, C16/24

47x50mm UG 47x75mm C16/24

Carcassing C24

47x100mm 47x125mm 47x150mm 47x175mm

47x200mm 47x225mm 47x250mm

75x100mm 75x150mm 75x200mm 75x225mm

Speciality Timber Dimensions

6x25mm Counterbatten / Plasterboard Lath

11x50mm Counterbatten


12x38mm Drip Batten

50x50mm Corner to Corner (Arris Rail)

50x100mm Corner to Corner (Arris Rail)

50x50mm Mopstick (Lead Roll)

- SR Timber "IMPORTED" products are manufactured at our own sawmill as well as carefully selected 3rd party production plants. Timber products should be protected whilst in store to prevent water saturation, this will assist in preventing sagging or twisting of the material.
- SR Timber "IMPORTED" products are available in various lengths ranging from 2.4m up to 5.4m, in 300mm increments. Carcassing is available from 2.4m up to 6.0m in 600mm increments.
- Produced from imported spruce (Whitewood) Abies Alba/Picea abies – WPCA or pine and (Redwood) Pinus sylvestris – PNSY or combined, all supplied as either FSC® Mix or PEFC, from fully certified or controlled wood resources. Ask for our FSC-certified products.
- High pressure Tanalith E preservative treated to use class relevant to the product type, as in accordance with recommendations given in BS 8417:2011+A1:2014. All SR Timber "Imported" products carry our standard 60 year service life certification, against insect attack and wood rotting fungi (when used correctly and installed above dpc level in buildings).
- We recommend that gloves are worn at all times when handling timber products.



PRODUCT DATA SHEET



SR Timber, Nunn Brook Road
Huthwaite, Sutton-in-Ashfield
Nottinghamshire, NG17 2HU

T: 01623 446800

E: sales@sr-timber.com

sr-timber.com