

Western Red Cedar Shingles

Blue Label 5X

Western red cedar shingles for roofing and cladding applications.

It is advised to check NFRC technical guidance notes on fixing cedar shingles and if treatment is advised, this tends to be calculated on the geographical location of which the product is to be fixed. Good practice is to also follow specification and fixers' advice.

After weathering they will adopt a silvery grey shade.

Cedar is naturally insect & rot resistant requiring no further treatment and sourced from sustainable forests in Western Canada.

Western Red Cedar.

Backed by The Cedar Shake and Shingle Bureau.

Colour	Natural, varying reddish brown to pale yellow
Grade	Blue Label, 100% Heartwood, 100% Edge Grain & 100% Clear
Size	400mm long, random widths 75mm - 350mm
Thickness	10mm at the butt, tapering
Profile	Sawn both sides, rectangular
Maximum Pitch	90°
Minimum Pitch	14°
Minimum Side Lap	38mm



Pitch	Maximum Gauge	Coverage m ² per Bundle
90°	190mm	3.47
22 - 90°	125mm	2.28
14 - 22°	95mm	1.73

Recommended fixings are stainless steel 31mm x 1.8mm annular ring nails.

Each shingle should be fixed with two nails.

As a rule of thumb 1kg of nails will be required for every 4 bundles of shingles.

Recommended roofing battens SRT GOLD® Roofing Batten BS 5534:2014+A2:2018

90°	25 x 50	5.3m - Battens per m ²
450mm centres	25 x 38	8.0m - Battens per m ²
600mm centres	25 x 38	10.5m - Battens per m ²

We recommend that gloves are worn at all times when handling timber products.



Promoting Sustainable Forest Management
www.pefc.co.uk



SR Timber, Nunn Brook Road, Huthwaite, Sutton-in-Ashfield, Nottinghamshire, NG17 2HU

01623 446 800 | sales@sr-timber.co.uk | sr-timber.co.uk